DESCALER

Uniconomy[®]
finding your solution with a smile

Issued: 29/06/24

Page 1

Revision No: 8

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

Product name: DESCALER

Use / description of product: De-scaler and brickwork cleaner.

Company name: Uniconomy Ltd / Sapphire Cleaning & Maintenance Solutions

Unit 1 Carter Building Red Marsh Inds Est Thornton Cleveleys

Lancashire FY5 4HP

Tel: 01253 854050 Fax: 01253 854049

2. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous ingredients: HYDROCHLORIC ACID

EINECS: 231-595-7 [C] R34; [Xi] R37

3. HAZARDS IDENTIFICATION

Main hazards: May cause burns. Irritating to respiratory system.

4. FIRST AID MEASURES (SYMPTOMS)

Skin contact: Irritation or pain may occur at the site of contact. There may be redness or whiteness of the skin

in the area of exposure. Blistering may occur. Severe burns may occur.

Eye contact: There may be irritation and redness. There may be severe pain. The eyes may water profusely.

Corneal burns may occur.

Ingestion: There may be soreness and redness of the mouth and throat. There may be difficulty

swallowing. Corrosive burns may appear around the lips. Nausea and stomach pain may occur.

There may be vomiting. Blood may be vomited.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. There may be

coughing and a sore throat. There may be congestion of the lungs causing severe shortness of

breath. There may be loss of consciousness.

4. FIRST AID MEASURES (ACTION)

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Drench the

affected skin with running water for 10 minutes or longer if substance is still on skin. Transfer to

hospital if there are burns or symptoms of poisoning.

Eye contact: Bathe the eye with running water for 15 minutes. Transfer to hospital for specialist examination.

Ingestion: Do not induce vomiting. Give 1 cup of water to drink every 10 minutes. If unconscious, check

for breathing and apply artificial respiration if necessary. If unconscious and breathing is OK,

place in the recovery position. Transfer to hospital as soon as possible.

[cont...]

DESCALER Page 2

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. If unconscious,

check for breathing and apply artificial respiration if necessary. If unconscious and breathing is

OK, place in the recovery position. If conscious, ensure the casualty sits or lies down. If

breathing becomes bubbly, have the casualty sit and provide oxygen if available. Transfer to

hospital as soon as possible.

5. FIRE-FIGHTING MEASURES

Extinguishing media: The product is non-combustible; appropriate extinguishing media for surrounding area should be

used in fire situations. Use water spray to cool containers.

Exposure hazards: Toxic or irritating fumes may be released at elevated temperatures.

Protection of fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin

and eyes.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions: Do not attempt to take action without suitable protective clothing - see section 8 of SDS.

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using sufficient appropriate absorbent

material. Failure to contain release must be reported to the local authority.

Clean-up procedures: Transfer to a suitable container. Wash down the drain with large amounts of water. Large

spillages should be contained with sand or earth and diluted to reduce fumes. Collect liquid by pumping into an emergency tank for safe disposal. Wash the spillage site with large amounts of

water.

7. HANDLING AND STORAGE

Handling requirements: Ensure there is sufficient ventilation of the area. Avoid direct contact with the substance. Safety

showers and eyewash facilities should be provided in areas where accidental exposure is

possible.

Storage conditions: Store in cool, well ventilated area. Keep container tightly closed.

Suitable packaging: Suitable materials are rubber lined steel, PVC, Polyethylene, Polypropylene, Glass, Stoneware,

PTFE. Unsuitable materials: corrodes most metals including stainless steel; certain GRP

fabrications depending on the type of resin.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Workplace exposure limits

WEL (15 min exposure limit): 5ppm (7mg/m3)

Hazardous ingredients: HYDROCHLORIC ACID

WEL (15 min exposure limit): 7.6 mg/m3

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: If Workplace Exposure Limit(s) listed above are exceeded, respiratory protection may be

required.

Issued: 29/08/19

SAFETY DATA SHEET

DESCALER





Page 3



Hand protection: In cases of prolonged contact wear protective gloves.

Eye protection: Wear safety glasses or goggles if risk of splashing. Ensure eye bath is to hand.

Skin protection: Skin Contact (other than hand contact) not likely. Remove contaminated clothing, wash with soap and water

Ensure safety shower is to hand

9. PHYSICAL AND CHEMICAL PROPERTIES

State: Liquid

Colour: Colourless to pale yellow.

Odour: Pungent

Solubility in water: Soluble

Boiling point/range°C: 97 Melting point/range°C: -60 Relative density: 1.14

10. STABILITY AND REACTIVITY

Stability: Will lose strength over time.

Materials to avoid: Strong acids. Strong bases. Oxidising agents. Amines. Can liberate harmful gases from certain

chemical salts e.g. cyanides, nitrites, sulphites, acetylides, carbides. Reacts with many metals to

liberate highly flammable hydrogen gas.

11. TOXICOLOGICAL INFORMATION

Routes of exposure: Causes irritation or burns to eyes, skin, respiratory system and internal organs if ingested. Over

exposure to vapour greatly above the Workplace Exposure Limit will result in coughing, wheezing, shortness of breath, chest pain and may cause lung damage. The irritant effects

provide adequate warning and exposure to harmful levels is unlikely to occur.

12. ECOLOGICAL INFORMATION

Mobility: Soluble in water.

Other adverse effects: Toxic to aquatic organisms. Lowering of pH below 5 will induce fatalities in aquatic life.

13. DISPOSAL CONSIDERATIONS

Disposal operations: Contact Uniconomy Ltd to arrange disposal. Tel 01253 854050

NB: The user's attention is drawn to the possible existence of regional or national regulations

regarding disposal.

14. TRANSPORT INFORMATION

ADR / RID

ADR Class: 8 **UN no:** 1789

Packing group: II Classification code: C1

Shipping name: HYDROCHLORIC ACID

DESCALER Page 4

Labelling: 8 Hazard ID no: 80



IMDG / IMO

UN no: 1789 Class: 8

Packing group: II EmS: F-A,S-B

Marine pollutant: NO Labelling: 8

IATA / ICAO

UN no: 1789 Class: 8

Packing group: II Packing instructions: 809(P&CA); 813(CAO)

Labelling: 8

15. REGULATORY INFORMATION

Hazard symbols: Corrosive.



Risk phrases: R34: Causes burns.

R37: Irritating to respiratory system.

Safety phrases: S2: Keep out of the reach of children.

S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical

advice.

S36/37/39: Wear suitable protective clothing, gloves and eye / face protection.

S45: In case of accident or if you feel unwell, seek medical advice immediately (show the label

where possible).

Note: The regulatory information given above only indicates the principal regulations specifically

applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all

applicable national, international and local regulations or provisions.

16. OTHER INFORMATION

Other information: Always use in accordance with manufacturer's directions.

This product belongs to Hazard Groups C and S under the HSE COSHH Essentials guidelines

(Publication HSG193).

This safety data sheet is prepared in accordance with EC Directive 2001/58/EC.

Risk phrases used in s.2: R34: Causes burns.

R37: Irritating to respiratory system.

[cont...]

DESCALER Page 5

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall

be used only as a guide. This company shall not be held liable for any damage resulting from

handling or from contact with the above product.