

PROVERSAL

Revision date: 09.06.24

Revision No: 6

Page: 1

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: PROVERSAL

Product code: UNI PVER

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: FOR PROFESSIONAL AND INDUSTRIAL USE ONLY. Aerosol solvent cleaner.

1.3. Details of the supplier of the safety data sheet

Company name: UNICONOMY LIMITED

Unit 1 & 2 Carter Building

- Brookside
- Thornton Cleveleys
- Lancashire
- FY5 4EZ
- Tel: 01253 854050
- Fax: 01253 854049
- Email: info@uniconomy.co.uk

1.4. Emergency telephone number

Emergency tel: 07860 323486 (Office hours only)

Section 2: Hazards identification

2.1. Classification of the substance or mixture

 Classification under CLP:
 Skin Irrit. 2: H315; STOT SE 3: H336; Aquatic Chronic 2: H411; Flam. Aerosol 1: H222; -:

 H229
 Most important adverse effects:
 Extremely flammable aerosol. Pressurised container: May burst if heated. Causes skin irritation. May cause drowsiness or dizziness. Toxic to aquatic life with long lasting effects.

2.2. Label elements

Label elements:	
Hazard statements:	H222: Extremely flammable aerosol.
	H229: Pressurised container: May burst if heated
	H315: Causes skin irritation.
	H336: May cause drowsiness or dizziness.
	H411: Toxic to aquatic life with long lasting effects.
Hazard pictograms:	GHS02: Flame

PROVERSAL

Page: 2

GHS07: Exclamation mark

GHS09: Environmental



Signal words: Danger

Precautionary statements:P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.
No smoking.P211: Do not spray on an open flame or other ignition source.P211: Do not spray on an open flame or other ignition source.
P251: Do not pierce or burn, even after use.P410+412: Protect from sunlight. Do not expose to temperatures exceeding 50 °C.P280: Wear protective gloves/protective clothing/eye protection/face protection.P260: Do not breathe spray.P302+352: IF ON SKIN: Wash with plenty of water/soap.P304+340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove
contact lenses, if present and easy to do. Continue rinsing.

2.3. Other hazards

Other hazards: In use, may form flammable / explosive vapour-air mixture.

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

HYDROCARBONS C6-C7 ISOALKANES, CYCLICS, <5% N-HEXANE, <0.1% BENZENE - REACH registered number(s): 01-2119475514-35-XXXX

EINECS	CAS	PBT / WEL	CLP Classification	Percent
265-151-9	64742-49-0	-	Flam. Liq. 2: H225; STOT SE 3: H336; Asp. Tox. 1: H304; Aquatic Chronic 2: H411; Skin Irrit. 2: H315	50-70%

BUTANE, <0.1% 1,3 BUTADIENE

203-448-7	106-97-8	Substance with a Community	Flam. Gas 1: H220; Press. Gas: H280	10-30%
		workplace exposure limit.		

PROPANE, <0.1% 1,3 BUTADIENE

200-827-9	74-98-6	Substance with a Community	Flam. Gas 1: H220; Press. Gas: H280	10-30%
		workplace exposure limit.		

PROVERSAL

Page: 3

200-662-2	67-64-1	-	Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336; -: EUH066	1-10%			
ion 4: First aid	d measures						
. Description o	of first aid me	asures					
\$	Skin contact:	Remove all contaminated clothes	and footwear immediately unless stuck to skin. Was	h			
			immediately with plenty of soap and water.				
			Bathe the eye with running water for 15 minutes. Consult a doctor.				
	-	Wash out mouth with water. Const					
		· ·	nsuring one's own safety whilst doing so. Consult a	doctor.			
2. Most importa	nt symptoms	s and effects, both acute and delay	/ed				
ę	Skin contact:	contact: There may be irritation and redness at the site of contact.					
	Eye contact:	There may be irritation and rednes	There may be irritation and redness. The eyes may water profusely.				
	Ingestion:	There may be soreness and redne	ess of the mouth and throat.				
	Inhalation:	-	at with a feeling of tightness in the chest. Exposure n	nay			
		cause coughing or wheezing.	cause coughing or wheezing.				
		Immediate effects can be expected					
3. Indication of	any immedia	te medical attention and special tr	eatment needed				
		Eye bathing equipment should be	available on the premises.				
tion 5: Fire-figl	nting measu	Ires					
.1. Extinguishing	y media						
Extingui	shing media:	Alcohol resistant foam. Water spra	ay. Carbon dioxide. Dry chemical powder. Use water	spray			
		to cool containers.					
.2. Special hazar	rds arising fr	om the substance or mixture					
Expos	ure hazards:	Highly flammable. In combustion e	emits toxic fumes. Forms explosive air-vapour mixtur	re.			
Слроз		Vapour may travel considerable distance to source of ignition and flash back. Aerosol cans					
Expos		vapour may travel considerable di	may explode during a fire, giving a high speed projectile.				
Expos			-	ouno			
.3. Advice for fire	e-fighters		-				
.3. Advice for fire		may explode during a fire, giving a	high speed projectile.				
.3. Advice for fire		may explode during a fire, giving a	-				
.3. Advice for fire Advice for	fire-fighters:	may explode during a fire, giving a Wear self-contained breathing app skin and eyes.	high speed projectile.				
.3. Advice for fire Advice for tion 6: Accider	fire-fighters: ntal release	may explode during a fire, giving a Wear self-contained breathing app skin and eyes. measures	a high speed projectile.				
.3. Advice for fire Advice for tion 6: Accider	fire-fighters: ntal release	may explode during a fire, giving a Wear self-contained breathing app skin and eyes.	a high speed projectile.				
.3. Advice for fire Advice for tion 6: Accider .1. Personal pred	fire-fighters: ntal release cautions, pro	may explode during a fire, giving a Wear self-contained breathing app skin and eyes. measures	a high speed projectile.	with			

contaminated area with signs and prevent access to unauthorised personnel. Eliminate all

PROVERSAL

Page: 4

sources of ignition. Cover leaking can until the discharge has stopped, before attempting cleanup operations.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal

by an appropriate method. Do not use equipment in clean-up procedure which may produce

sparks. Leaking material will evaporate leaving no residues.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of mists in the air. Smoking is forbidden. Use non-sparking tools.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep away from sources of ignition. Keep away from direct sunlight.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

HYDROCARBONS C6-C7 ISOALKANES, CYCLICS, <5% N-HEXANE, <0.1% BENZENE

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	1100 mg/m3	2200 mg/m3	-	-

BUTANE, <0.1% 1,3 BUTADIENE

UK	1450 mg/m3	1810 mg/m3	-	-

PROPANE, <0.1% 1,3 BUTADIENE

UK Asphyxiating Asphyxiatin	-
-----------------------------	---

PROVERSAL

ACETONE						
UK	12	210 mg/m3	3620 mg/m3	-		-
DNEL/PNEC Valu	DNEL/PNEC Values					
	DNEL / PNEC No data available.					
8.2. Exposure co	ntrols					
Engineerir	ng measures:	Ensure the	re is sufficient ventilation of	the area. Ensure lighting and	elect	rical equipment are
not a source of ignition.						
Respirator	Respiratory protection: Self-contained breathing apparatus must be available in case of emergency.					CV.
	d protection:				3	- ,-
	-		ses. Ensure eye bath is to h	and.		
	n protection:		-			
Section 9: Physica	-		-			
Section 9. Filysica						
9.1. Information of	on basic physi	ical and che	emical properties			
	State:	Aerosol				
	Colour:	Brown				
	Odour:	Solvents,m	ixed.			
Eva	ooration rate:	Not applicab	le			
Solub	ility in water:	Insoluble				
	Viscosity:	Non-viscou	IS			
Boiling p	oint/range°C:	Not applica	ble.	Melting point/range	e°C:	Not applicable.
Flammability lin	nits %: lower:	: 0.9				
F	lash point°C:	-40		Part.coeff. n-octanol/wa	ater:	Not applicable.
Autofla	mmability°C:	>230		Vapour press	ure:	Not applicable.
Rela	ative density:	Not applica	ıble.		pH:	Not applicable.
	VOC g/l:	No data av	ailable.			
9.2. Other inform	ation					

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions. Stable at room temperature.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

Page: 5

PROVERSAL

10.4. Conditions to avoid

Conditions to avoid: Heat. Hot surfaces. Sources of ignition. Flames. Direct sunlight.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

HYDROCARBONS C6-C7 ISOALKANES, CYCLICS, <5% N-HEXANE, <0.1% BENZENE

DERMAL	RBT	LD50	3350	mg/kg
ORAL	RAT	LD50	16750	mg/kg
VAPOURS	RAT	4H LC50	259	g/l

ACETONE

IVN	RAT	LD50	5500	mg/kg
ORL	MUS	LD50	3000	mg/kg
ORL	RAT	LD50	5800	mg/kg

Relevant hazards for product:

Hazard	Route	Basis
Skin corrosion/irritation	DRM	Hazardous: calculated
STOT-single exposure	-	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

Section 12: Ecological information

12.1. Toxicity

PROVERSAL

Page: 7

Hazardous ingredients:

HYDROCARBONS C6-C7 ISOALKANES, CYCLICS, <5% N-HEXANE, <0.1% BENZENE

Daphnia magna	48H EC50	17.06	mg/l
RAINBOW TROUT (Oncorhynchus mykiss)	96H LC50	9.766	mg/l

ACETONE

BLUEGILL (Lepomis macrochirus)	LC50	8300	mg/l	
--------------------------------	------	------	------	--

12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil. Volatile. Insoluble in water. Floats on water. Vapour is heavier than

air.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Toxic to aquatic organisms.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations:	Transfer to a suitable container and arrange for collection by specialised disposal company.	
Recovery operations:	erations: Recycling/reclamation of metals and metal compounds.	
Waste code number:	16 05 05	
Disposal of packaging:	Dispose of as normal industrial waste. Empty cans must not be burned because of explosion	
	hazard.	
NB:	The user's attention is drawn to the possible existence of regional or national regulations	

regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN1950

14.2. UN proper shipping name

Shipping name: AEROSOLS

PROVERSAL

14.3. Transport hazard class(es) Transport class: 2 Marine pollutant: No Special precautions: No special precautions. Tunnel code: D Transport category: 2 the supplier. Other information Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No 2015/830. IMPORTANT NOTE: Risk phases in this section below relate to the INDIVIDUAL COMPONENTS in the formulation when used at their FULL CONCENTRATIONS, and not at the reduced levels in the mixed product. See sections 2 and 3 for the calculated hazard and risk phrases for the blended product. Phrases used in s.2 and s.3: EUH066: Repeated exposure may cause skin dryness or cracking.

H220: Extremely flammable gas.

H222: Extremely flammable aerosol.

H225: Highly flammable liquid and vapour.

H229: Pressurised container: May burst if heated

H304: May be fatal if swallowed and enters airways.

H315: Causes skin irritation.

H319: Causes serious eye irritation.

H336: May cause drowsiness or dizziness.

H411: Toxic to aquatic life with long lasting effects.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product. For professional and industrial use only

Page: 8

14.4. Packing group

14.5. Environmental hazards

Environmentally hazardous: Yes

14.6. Special precautions for user

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by

Section 16: Other information