

# SAFETY DATA SHEET

PRO-SPOT



Page 1

Issued: 13/03/15

Revision No: 6

## 1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

**Product name:** PRO-SPOT

**Use / description of product:** Survey Marker Spray

**Company name:** Uniconomy Ltd

Unit 1 Carter Building, Brookside

Red Marsh Inds Est

Thornton, Cleveleys

Lancashire

FY5 4EZ

Tel: 01253 854050

Fax: 01253 854049

## 2. COMPOSITION / INFORMATION ON INGREDIENTS

**Hazardous ingredients:** N-BUTYL ACETATE

EINECS: 204-658-1 CAS: 123-86-4 [-] R10; [-] R66; [-] R67

- BUTANE

EINECS: 203-448-7 CAS: 106-97-8

[F+] R12

- PROPANE

EINECS: 200-827-9 CAS: 74-98-6

[F+] R12

## 3. HAZARDS IDENTIFICATION

**Main hazards:** Extremely flammable.

## 4. FIRST AID MEASURES (SYMPTOMS)

**Skin contact:** In cases of prolonged contact there may be irritation and redness at the site of contact.

**Eye contact:** May cause temporary discomfort.

**Ingestion:** Aerosol packs make the possibility of ingestion unlikely, however if this should occur, irritation of mouth/throat, nausea and stomach pain may result.

**Inhalation:** No undue effects under normal circumstances.

## 4. FIRST AID MEASURES (ACTION)

**Skin contact:** Wash with soap and water. Seek medical advice if irritation develops.

**Eye contact:** Rinse with water for 10 minutes and seek medical advice if irritation persists.

**Ingestion:** If affected, seek medical advice.

**Inhalation:** If affected, remove to fresh air. Seek medical attention.

[cont...]

**SAFETY DATA SHEET**

PRO-SPOT

**5. FIRE-FIGHTING MEASURES**

**Extinguishing media:** Carbon dioxide. Alcohol resistant foam.

**Exposure hazards:** Extremely flammable.

**Protection of fire-fighters:** Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

**6. ACCIDENTAL RELEASE MEASURES**

**Personal precautions:** Eliminate all sources of ignition. Wear appropriate protective clothing.

**Environmental precautions:** Do not discharge into drains or rivers. Contain the spillage using sufficient appropriate absorbent material.

**Clean-up procedures:** If spillage is from leaking/punctured cans, ensure adequate ventilation and allow propellant to evaporate. Wipe up liquid spillage with absorbent material and dispose of safely.

**7. HANDLING AND STORAGE**

**Handling requirements:** Handle in accordance with standard good housekeeping procedures.

**Storage conditions:** Store in a cool, well ventilated area, below 50°C. Keep away from sources of ignition.

**8. EXPOSURE CONTROLS / PERSONAL PROTECTION**

**Hazardous ingredients:** BUTANE

WEL (8 hr exposure limit): 1450 mg/m<sup>3</sup> WEL (15 min exposure limit): 1810 mg/m<sup>3</sup>

- PROPANE

WEL (8 hr exposure limit): 1800 mg/m<sup>3</sup> WEL (15 min exposure limit): 7200 mg/m<sup>3</sup>

**Engineering measures:** No specific engineering measures are necessary.

**Hand protection:** Protective gloves.

**Eye protection:** Safety goggles.

**9. PHYSICAL AND CHEMICAL PROPERTIES**

**State:** Aerosol

**Colour:** Various paint colours

**Odour:** Celulose

**Oxidising:** Non-oxidising (by EC criteria)

**Solubility in water:** Miscible

**Flammability limits %: lower:** 0.8

**upper:** 9.0

**Flash point°C:** -40

**10. STABILITY AND REACTIVITY**

**Stability:** Stable under normal conditions.

**Conditions to avoid:** Sources of ignition. Flames.

**Materials to avoid:** Oxidising agents.

**11. TOXICOLOGICAL INFORMATION**

**Routes of exposure:** No adverse effects should be experienced under normal circumstances.

**12. ECOLOGICAL INFORMATION**

**Mobility:** Readily dispersible in water.

**13. DISPOSAL CONSIDERATIONS**

**Disposal operations:** Contact Uniconomy to arrange disposal. Tel 01253 854050

**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

**14. TRANSPORT INFORMATION****ADR / RID**

**UN no:** 1950

**ADR Class:** 2

**Classification code:** 5F

**Shipping name:** AEROSOLS

**Labelling:** 2.1

**IMDG / IMO**

**UN no:** 1950

**Class:** 2

**EmS:** F-D,S-U

**Marine pollutant:** .

**Labelling:** 2.1

**IATA / ICAO**

**UN no:** 1950

**Class:** 2

**Labelling:** 2.1

**15. REGULATORY INFORMATION**

**Hazard symbols:** Extremely flammable.



**Risk phrases:** R12: Extremely flammable.

**Safety phrases:** S2: Keep out of the reach of children.

S16: Keep away from sources of ignition - No smoking.

S45: In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

## SAFETY DATA SHEET

PRO-SPOT

**Precautionary phrases:** Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking. Keep out of the reach of children.

**Note:** The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions.

### 16. OTHER INFORMATION

**Other information:** Always use in accordance with manufacturer's directions.

This safety data sheet is prepared in accordance with EC Directive 2001/58/EC.

**Risk phrases used in s.2:** R22: Harmful if swallowed.

R36/38: Irritating to eyes and skin.

R12: Extremely flammable.

**Legal disclaimer:** The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.