

PRO-GRAFF

Page: 1 Compilation date: 23/02/2016 Revision date: 10.06.24 Revision No: 4

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: PRO-GRAFF

Product code: UNIPGRA

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: FOR PROFESSIONAL AND INDUSTRIAL USE ONLY. Aerosol solvent cleaner.

1.3. Details of the supplier of the safety data sheet

Company name:	UNICONOMY LIMITED
	Unit 4Chester Court
	Thornton Cleveleys
	Lancashire
	FY5 4EZ
	United Kingdom

Tel: 01253 854050

Fax: 01253 854049

Email: info@uniconomy.co.uk

1.4. Emergency telephone number

Emergency tel: 07860 323486 Office Hours Only

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP:	Skin Irrit. 2: H315; STOT SE 3: H336; Aquatic Chronic 2: H411; Flam. Aerosol 1: H222; -:
	H229
Most important adverse effects:	Extremely flammable aerosol. Pressurised container: May burst if heated. Causes skin
	irritation. May cause drowsiness or dizziness. Toxic to aquatic life with long lasting effects.

2.2. Label elements

Label elements:	
Hazard statements:	H222: Extremely flammable aerosol.
	H229: Pressurised container: May burst if heated
	H315: Causes skin irritation.
	H336: May cause drowsiness or dizziness.
	H411: Toxic to aquatic life with long lasting effects.
Hazard pictograms:	GHS02: Flame

PRO-GRAFF

Page: 2

GHS07: Exclamation mark GHS09: Environmental Signal words: Danger Precautionary statements: P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211: Do not spray on an open flame or other ignition source. P251: Do not pierce or burn, even after use. P410+412: Protect from sunlight. Do not expose to temperatures exceeding 50 °C. P102: Keep out of reach of children. P260: Do not breathe vapours. P280: Wear protective gloves/protective clothing/eye protection/face protection. P302+352: IF ON SKIN: Wash with plenty of water/soap. P304+340: IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

2.3. Other hazards

Other hazards: In use, may form flammable / explosive vapour-air mixture.

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

HYDROCARBONS C6-C7 ISOALKANES, CYCLICS, <5% N-HEXANE, <0.1% BENZENE - REACH registered number(s): 01-2119475514-35-XXXX

	EINECS	CAS	PBT / WEL	CLP Classification	Percent
2	265-151-9	64742-49-0	-	Flam. Liq. 2: H225; STOT SE 3: H336; Asp. Tox. 1: H304; Aquatic Chronic 2:	70-90%
				H411; Skin Irrit. 2: H315	

BUTANE, <0.1% 1,3 BUTADIENE

203-448-7	106-97-8	Substance with a Community	Flam. Gas 1: H220; Press. Gas: H280	10-30%
		workplace exposure limit.		

PRO-GRAFF

Page: 3

PROPANE, <0.	.1% 1,3 BUTADI	IENE		
200-827-9	74-98-6	Substance with a Community workplace exposure limit.	Flam. Gas 1: H220; Press. Gas: H280	10-30%
ection 4: First ai	id measures			
4.1. Description	of first aid mea	isures		
	Skin contact:	Wash immediately with plenty of soap an	nd water.	
	Eye contact:	Bathe the eye with running water for 15 n	ninutes.	
Ingestion: Wash out mouth with water. Do not induce vomiting. If conscious, give half a litre of water to			ater to	
	drink immediately.			
	Inhalation:	Remove casualty from exposure ensuring	g one's own safety whilst doing so.	
4.2. Most import	ant symptoms	and effects, both acute and delayed		
	Skin contact:	There may be irritation and redness at th	e site of contact.	
Eye contact: There may be irritation and redness. The eyes may water profusely.				
Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach pain				
	-	may occur. There may be vomiting.		
	Inhalation:	There may be irritation of the throat with	a feeling of tightness in the chest.	
Delayed / imme		Immediate effects can be expected after		
-		e medical attention and special treatme	·	
Immediate / spec				
ection 5: Fire-fig	hting measu	res		
5.1. Extinguishin	ng media			
Extingu	ishing media:	Alcohol or polymer foam. Carbon dioxide	e. Dry chemical powder. Use water spray to co	loc
		containers.		
5.2. Special hazards arising from the substance or mixture				
Ехро	Exposure hazards: Highly flammable. In combustion emits toxic fumes. Forms explosive air-vapour mixture.			re.
	Vapour may travel considerable distance to source of ignition and flash back. Aerosol cans			cans
	may explode during a fire, giving a high speed projectile.			
5.3. Advice for fire-fighters				
		Wear self-contained breathing apparatur	s. Wear protective clothing to prevent contact	with
	The lighters.	skin and eyes.	s. Wear protective dourning to prevent contact	WIUT
	- I I	·		
Section 6: Accidental release measures				
ection 6: Accide	ental release r			
		ective equipment and emergency proce	edures	

downwind. If outside keep bystanders upwind and away from danger point. Mark out the

contaminated area with signs and prevent access to unauthorised personnel. Eliminate all

PRO-GRAFF

Page: 4

sources of ignition. Cover leaking can until the discharge has stopped, before attempting cleanup operations.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal

by an appropriate method. Do not use equipment in clean-up procedure which may produce

sparks. Wash the ground with an appropriate self-emulsifying solvent.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of mists in the air. Smoking is forbidden. Use non-sparking tools.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep away from sources of ignition. Keep away from direct sunlight.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

HYDROCARBONS C6-C7 ISOALKANES, CYCLICS, <5% N-HEXANE, <0.1% BENZENE

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	1100 mg/m3	2200 mg/m3	-	-

BUTANE, <0.1% 1,3 BUTADIENE

	UK	1450 mg/m3	1810 mg/m3	-	-
--	----	------------	------------	---	---

PROPANE, <0.1% 1,3 BUTADIENE

UK Asphyxiating Asphyxiating -	-
--------------------------------	---

DNEL/PNEC Values

DNEL / PNEC No data available.

PRO-GRAFF

8.2. Exposure controls

Engineering measures:	Ensure there is sufficient ventilation of the area. Ensure lighting and electrical equipment are
	not a source of ignition.
Respiratory protection:	Self-contained breathing apparatus must be available in case of emergency.
Hand protection:	Impermeable gloves.
Eye protection:	Safety glasses. Ensure eye bath is to hand.
Skin protection:	Impermeable protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State:	Aerosol	
Colour:	Colourless	
Odour:	Paraffinic	
Evaporation rate:	Fast	
Solubility in water:	Insoluble	
Viscosity:	Non-viscous	
Boiling point/range°C:	Not applicable. Melting point/range°C	Not applicable.
Flammability limits %: lower:	0.9 upper	8.0
Flash point°C:	<0 Part.coeff. n-octanol/water	Not applicable.
Autoflammability°C:	>230 Vapour pressure	Not applicable.
Relative density:	Not applicable. PH	Not applicable.
VOC g/l:	Not applicable.	

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions. Stable at room temperature.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat. Hot surfaces. Sources of ignition. Flames. Direct sunlight.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

Page: 5

PRO-GRAFF

Page: 6

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

HYDROCARBONS C6-C7 ISOALKANES, CYCLICS, <5% N-HEXANE, <0.1% BENZENE

DERMAL	RBT	LD50	3350	mg/kg
ORAL	RAT	LD50	16750	mg/kg
VAPOURS	RAT	4H LC50	259	g/l

Relevant hazards for product:

Hazard	Route	Basis
Skin corrosion/irritation	DRM	Hazardous: calculated
STOT-single exposure	-	Hazardous: calculated

Symptoms / routes of exposure

Skin contact:There may be irritation and redness at the site of contact.Eye contact:There may be irritation and redness. The eyes may water profusely.Ingestion:There may be soreness and redness of the mouth and throat. Nausea and stomach pain
may occur. There may be vomiting.Inhalation:There may be irritation of the throat with a feeling of tightness in the chest.Delayed / immediate effects:Immediate effects can be expected after short-term exposure.

Section 12: Ecological information

12.1. Toxicity

Hazardous ingredients:

HYDROCARBONS C6-C7 ISOALKANES, CYCLICS, <5% N-HEXANE, <0.1% BENZENE

Daphnia magna	48H EC50	17.06	mg/l
RAINBOW TROUT (Oncorhynchus mykiss)	96H LC50	9.766	mg/l

12.2. Persistence and degradability

Persistence and degradability: Not readily biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil. Volatile. Insoluble in water. Floats on water. Vapour is heavier than

air.

PRO-GRAFF

Page: 7

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Toxic to aquatic organisms. Toxic to soil organisms.

Section 13: Disposal considerations

13.1. Waste treatment methods					
-					
Disposal operations:	Transfer to a suitable container and arrange for collection by specialised disposal company.				
Recovery operations:	Recycling/reclamation of metals and metal compounds.				
Waste code number:	16 05 05				
Disposal of packaging:	Dispose of as normal industrial waste. Empty cans must not be burned because of explosion				
	hazard.				
NB:	The user's attention is drawn to the possible existence of regional or national regulations				

regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN1950

14.2. UN proper shipping name

Shipping name: AEROSOLS

14.3. Transport hazard class(es)

Transport class: 2

14.4. Packing group

14.5. Environmental hazards

Environmentally hazardous: Yes

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: D

Transport category: 2

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by

the supplier.

Marine pollutant: No

PRO-GRAFF

Section 16: Other information

ther information	
Other information:	This safety data sheet is prepared in accordance with Commission Regulation (EU) No
	2015/830.
	IMPORTANT NOTE:
	Risk phases in this section below relate to the INDIVIDUAL COMPONENTS in the formulation
	when used at their FULL CONCENTRATIONS, and not at the reduced levels in the mixed
	product.
	See sections 2 and 3 for the calculated hazard and risk phrases for the blended product.
Phrases used in s.2 and s.3:	H220: Extremely flammable gas.
	H222: Extremely flammable aerosol.
	H225: Highly flammable liquid and vapour.
	H229: Pressurised container: May burst if heated
	H304: May be fatal if swallowed and enters airways.
	H315: Causes skin irritation.
	H336: May cause drowsiness or dizziness.
	H411: Toxic to aquatic life with long lasting effects.
Legal disclaimer:	The above information is believed to be correct but does not purport to be all inclusive and
	shall be used only as a guide. This company shall not be held liable for any damage resulting
	from handling or from contact with the above product. For professional and industrial use
	only.