#### SAFETY DATA SHEET

MULTI LUBE (AEROSOL)

Issued: 12/05/14

Revision No: 9

Page 1



## 1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

Product name: MULTI LUBE

Use / description of product: Release agent.

Company name: Uniconomy Ltd

Unit 4 Chester Court Red Marsh Ind Est Thornton Cleveleys

Lancashire FY5 4EZ

Tel: 01253 854050

#### 2. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous ingredients: NAPHTHA (PETROLEUM), HYDROTREATED HEAVY 70-90%

[-] R10; [Xn] R65; [-] R66 CAS: 64742-49-0

EINECS: 203-448-7 CAS: 106-97-8 [F+] R12 **BUTANE 1-10%** 

PROPANE 1-10% EINECS: 200-827-9 CAS: 74-98-6 [F+] R12

ALIPHATIC CYCLOPARAFFINIC HYDROCARBON EINECS: 265-150-3 CAS: 64742-48-9 [F+] R12

SODIUM SULPHONATES CAS: 68608-26-4 R41 CALCIUM SULPHONATES CAS: 57855-77-3 R36/38

#### 3. HAZARDS IDENTIFICATION

Main hazards: Extremely flammable. Repeated exposure may cause skin dryness or cracking.

Other hazards: In use, may form flammable / explosive vapour-air mixture.

#### 4. FIRST AID MEASURES (SYMPTOMS)

**Skin contact:** There may be irritation and redness at the site of contact.

**Eye contact:** There may be irritation and redness.

Ingestion: Aerosol packs make the possibility of ingestion unlikely, however if this should occur, irritation of

mouth/throat, nausea and stomach pain may result.

Inhalation: Inhalation of high levels of vapour may cause upper respiratory tract irritation. Drowsiness or

mental confusion may occur. There may be loss of consciousness.

## 4. FIRST AID MEASURES (ACTION)

Skin contact: Wash with soap and water. Seek medical advice if irritation develops.

Eye contact: Rinse with water for 10 minutes and seek medical advice if irritation persists.

**Ingestion:** If affected, seek medical advice.

#### SAFETY DATA SHEET

MULTI LUBE Page 2

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. If unconscious,

check for breathing and apply artificial respiration if necessary. If unconscious and breathing is

OK, place in the recovery position. If conscious, ensure the casualty sits or lies down. If

breathing becomes bubbly, have the casualty sit and provide oxygen if available. Transfer to

hospital as soon as possible.

## 5. FIRE-FIGHTING MEASURES

Extinguishing media: Carbon dioxide. Alcohol or polymer foam. Dry chemical powder.

**Exposure hazards:** In combustion emits toxic fumes.

Protection of fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin

and eyes.

#### 6. ACCIDENTAL RELEASE MEASURES

Personal precautions: Eliminate all sources of ignition. Mark out the contaminated area with signs and prevent access

to unauthorised personnel.

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using sufficient appropriate absorbent

material.

Clean-up procedures: If spillage is from leaking/punctured cans, ensure adequate ventilation and allow propellant to

evaporate. Wipe up liquid spillage with absorbent material and dispose of safely.

## 7. HANDLING AND STORAGE

Handling requirements: Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Smoking is

forbidden.

**Storage conditions:** Store in a cool, well ventilated area, below 50'C.

# 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Hazardous ingredients: NAPHTHA (PETROLEUM), HYDROTREATED HEAVY

WEL (8 hr exposure limit): 1000mg/m3

BUTANE

WEL (8 hr exposure limit): 1450 mg/m3 WEL (15 min exposure limit): 1810 mg/m3

PROPANE

WEL (8 hr exposure limit): 1800 mg/m3 WEL (15 min exposure limit): 7200 mg/m3

**Engineering measures:** Ensure there is sufficient ventilation of the area. Do not handle in a confined space.

Respiratory protection: If Workplace Exposure Limit(s) listed above are exceeded, respiratory protection may be

required.

Hand protection: In cases of prolonged use wear protective gloves.

Eye protection: Wear safety glasses or goggles if risk of splashing.

**Skin protection:** Skin contact unlikely under normal use.

MULTI LUBE Page 3

## 9. PHYSICAL AND CHEMICAL PROPERTIES

State: Aerosol
Colour: Brown
Odour: Pleasant

Oxidising: Non-oxidising (by EC criteria)

Solubility in water: Insoluble

Flammability limits %: lower: 0.6

upper: 9.0
Flash point°C: -40
Autoflammability°C: >230

#### 10. STABILITY AND REACTIVITY

**Stability:** Stable under normal conditions.

Conditions to avoid: Heat. Sources of ignition. Flames.

Materials to avoid: Strong acids. Strong bases. Oxidising agents.

Haz. decomp. products: In combustion emits toxic fumes of carbon dioxide / carbon monoxide.

## 11. TOXICOLOGICAL INFORMATION

Hazardous ingredients: NAPHTHA (PETROLEUM), HYDROTREATED HEAVY

ORL RAT LD50 >5000 mg/kg

Routes of exposure: Exposure to high levels of vapour may cause drowsiness, dizziness, nausea, headaches,

vomiting. Prolonged contact with skin may cause irritation leading to dermatitis in extreme

cases.

# 12. ECOLOGICAL INFORMATION

Mobility: Insoluble in water.

Other adverse effects: The aerosol contents are potentially harmful to aquatic organisms.

# 13. DISPOSAL CONSIDERATIONS

**Disposal operations:** Contact Uniconomy to arrange disposal.Tel 01253 854050

NB: The user's attention is drawn to the possible existence of regional or national regulations

regarding disposal.

# 14. TRANSPORT INFORMATION

## ADR / RID

**UN no:** 1950 **ADR Class:** 2

Classification code: 5F

Shipping name: AEROSOLS

Labelling: 2.1



#### SAFETY DATA SHEET

MULTI LUBE Page 4

IMDG / IMO

UN no: 1950 Class: 2

EmS: F-D,S-U Marine pollutant: .

Labelling: 2.1

IATA / ICAO

UN no: 1950 Class: 2

Labelling: 2.1

## 15. REGULATORY INFORMATION

**Hazard symbols:** Extremely flammable.



**Risk phrases:** R12: Extremely flammable.

R66: Repeated exposure may cause skin dryness or cracking.

**Safety phrases:** S2: Keep out of the reach of children.

S16: Keep away from sources of ignition - No smoking.

S23: Do not breathe vapour/spray.

S51: Use only in well-ventilated areas.

Precautionary phrases: Pressurized container: protect from sunlight and do not expose to temperatures exceeding

50°C. Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material. Keep away from sources of

ignition - No smoking. Keep out of the reach of children.

Note: The regulatory information given above only indicates the principal regulations specifically

applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all

applicable national, international and local regulations or provisions.

## 16. OTHER INFORMATION

Other information: Always use in accordance with manufacturer's directions.

This safety data sheet is prepared in accordance with EC Directive 2001/58/EC.

**Risk phrases used in s.2:** R10: Flammable.

R65: Harmful: may cause lung damage if swallowed.

R66: Repeated exposure may cause skin dryness or cracking.

R12: Extremely flammable.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall

be used only as a guide. This company shall not be held liable for any damage resulting from

handling or from contact with the above product.