

# SAFETY DATA SHEET

GREASE - IT

Page 1



Issued: 15/06/18

Revision 7

## 1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

**Product name:** GREASE - IT

**Use / description of product:** Grease lubricant.

**Company name:** Uniconomy Ltd

Unit 1 Carter Building, Brookside

Red Marsh Inds Est

Thornton, Cleveleys

Lancashire

FY5 4EZ

Tel: 01253 854050

Fax: 01253 854049

## 2. COMPOSITION / INFORMATION ON INGREDIENTS

**Hazardous ingredients:** NAPHTHA (PETROLEUM), HYDROTREATED LIGHT; LOW BOILING POINT HYDROGEN  
30-50%

CAS: 64742-49-0

[F] R11; [Xn] R65; [Xi] R38; [N] R51/53; [-] R67

- BUTANE 10-30%

EINECS: 203-448-7 CAS: 106-97-8

[F+] R12

- PROPANE 10-30%

EINECS: 200-827-9 CAS: 74-98-6

[F+] R12

## 3. HAZARDS IDENTIFICATION

**Main hazards:** Extremely flammable. Irritating to skin. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Vapours may cause drowsiness and dizziness.

**Other hazards:** In use, may form flammable / explosive vapour-air mixture.

## 4. FIRST AID MEASURES (SYMPTOMS)

**Skin contact:** There may be irritation and redness at the site of contact. Prolonged or repeated contact may defat the skin leading to dermatitis.

**Eye contact:** There may be irritation and redness.

**Ingestion:** Aerosol packs make the possibility of ingestion unlikely, however if this should occur, irritation of mouth/throat, nausea and stomach pain may result.

**Inhalation:** Inhalation of high levels of vapour may cause upper respiratory tract irritation. Exposure may cause coughing or wheezing. There may be loss of consciousness.

[cont...]

**SAFETY DATA SHEET**

GREASE - IT

**4. FIRST AID MEASURES (ACTION)**

**Skin contact:** Wash skin thoroughly with soap and warm water. Dry skin and apply replenishing cream. Seek medical advice if irritation develops.

**Eye contact:** Rinse with water for 10 minutes and seek medical advice if irritation persists.

**Ingestion:** If affected, seek medical advice.

**Inhalation:** Remove to fresh air. Perform artificial respiration if breathing has stopped. Keep the affected person warm and at rest. Get prompt medical attention.

**5. FIRE-FIGHTING MEASURES**

**Extinguishing media:** Carbon dioxide. Alcohol resistant foam.

**Exposure hazards:** In combustion emits toxic fumes.

**Protection of fire-fighters:** Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

**6. ACCIDENTAL RELEASE MEASURES**

**Personal precautions:** Eliminate all sources of ignition. Mark out the contaminated area with signs and prevent access to unauthorised personnel.

**Environmental precautions:** Do not discharge into drains or rivers. Contain the spillage using sufficient appropriate absorbent material.

**Clean-up procedures:** If spillage is from leaking/punctured cans, ensure adequate ventilation and allow propellant to evaporate. Wipe up liquid spillage with absorbent material and dispose of safely.

**7. HANDLING AND STORAGE**

**Handling requirements:** Ensure there is sufficient ventilation of the area. Avoid direct contact with the substance. Smoking is forbidden.

**Storage conditions:** Store in a cool, well ventilated area, below 50°C. Keep away from sources of ignition.

**8. EXPOSURE CONTROLS / PERSONAL PROTECTION**

**Hazardous ingredients:** NAPHTHA (PETROLEUM), HYDROTREATED LIGHT; LOW BOILING POINT HYDROGEN  
WEL (8 hr exposure limit): 1000 mg/m<sup>3</sup>

- BUTANE

WEL (8 hr exposure limit): 1450 mg/m<sup>3</sup> WEL (15 min exposure limit): 1810 mg/m<sup>3</sup>

- PROPANE

WEL (8 hr exposure limit): 1800 mg/m<sup>3</sup> WEL (15 min exposure limit): 7200 mg/m<sup>3</sup>

**Engineering measures:** Ensure there is sufficient ventilation of the area. Naphtha (Petroleum), Hydrotreated Light; Low Boiling Hydrogen OEL: 1000mg/m<sup>3</sup> (8h TWA-suggested).

**Respiratory protection:** If Workplace Exposure Limit(s) listed above are exceeded, respiratory protection may be required.

**Hand protection:** Contact not likely under normal conditions.

**Eye protection:** Contact not likely under normal conditions..

**Skin protection:** Contact not likely under normal conditions.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

**State:** Aerosol

**Colour:** White

**Odour:** Paraffinic

**Oxidising:** Non-oxidising (by EC criteria)

**Solubility in water:** Insoluble

**Flammability limits %: lower:** 0.8

**upper:** 9.0

**Flash point°C:** -40

## 10. STABILITY AND REACTIVITY

**Stability:** Stable under normal conditions.

**Conditions to avoid:** Hot surfaces. Sources of ignition. Flames.

**Materials to avoid:** Strong oxidising agents.

**Haz. decomp. products:** In combustion emits toxic fumes.

## 11. TOXICOLOGICAL INFORMATION

**Routes of exposure:** Refer to section 4 of SDS for routes of exposure and corresponding symptoms.

## 12. ECOLOGICAL INFORMATION

**Mobility:** Readily absorbed into soil.

**Other adverse effects:** The aerosol contents are potentially harmful to aquatic organisms.

## 13. DISPOSAL CONSIDERATIONS

**Disposal operations:** Contact Uniconomy Ltd to arrange disposal.Tel 01253 854050

**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

## 14. TRANSPORT INFORMATION

### ADR / RID

**UN no:** 1950

**ADR Class:** 2

**Classification code:** 5F

**Shipping name:** AEROSOLS

**Labelling:** 2.1



**SAFETY DATA SHEET**

GREASE - IT

**IMDG / IMO**

**UN no:** 1950 **Class:** 2  
**EmS:** F-D,S-U **Marine pollutant:** .  
**Labelling:** 2.1

**IATA / ICAO**

**UN no:** 1950 **Class:** 2  
**Labelling:** 2.1

**15. REGULATORY INFORMATION**

**Hazard symbols:** Extremely flammable.  
 Irritating.  
 Dangerous for the environment.



**Risk phrases:** R12: Extremely flammable.  
 R38: Irritating to skin.  
 R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.  
 R67: Vapours may cause drowsiness and dizziness.

**Safety phrases:** S2: Keep out of the reach of children.  
 S23: Do not breathe vapour/spray.  
 S36/37: Wear suitable protective clothing and gloves.  
 S51: Use only in well-ventilated areas.  
 S61: Avoid release to the environment. Refer to special instructions / safety data sheets.

**Precautionary phrases:** Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.  
 Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking. Keep out of the reach of children.

**Note:** The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions.

**16. OTHER INFORMATION**

**Other information:** Always use in accordance with manufacturer's directions.  
 This safety data sheet is prepared in accordance with EC Directive 2001/58/EC.

**Risk phrases used in s.2:** R11: Highly flammable.

## SAFETY DATA SHEET

GREASE - IT

R65: Harmful: may cause lung damage if swallowed.

R38: Irritating to skin.

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R67: Vapours may cause drowsiness and dizziness.

R12: Extremely flammable.

**Legal disclaimer:** The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.