ALL LUBE (AEROSOL)



Page 1 Issued: 12/02/15 Revision No: 5

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

Product name: ALL LUBE

Use / description of product: Release agent. Company name: Uniconomy Ltd 4, Chester Court Red Marsh Inds Est Thornton ,Cleveleys Lancashire FY5 4EZ Tel: 01253 854050 Fax: 01253 854049

2. COMPOSITION / INFORMATION ON INGREDIENTS

 Hazardous ingredients:
 NAPHTHA (PETROLEUM), HYDROTREATED HEAVY 70-90%

 CAS:
 64742-49-0
 [-] R10; [Xn] R65; [-] R66

 BUTANE
 1-10%
 EINECS: 203-448-7
 CAS: 106-97-8
 [F+] R12

 PROPANE
 1-10%
 EINECS: 200-827-9
 CAS: 74-98-6
 [F+] R12

 ALIPHATIC CYCLOPARAFFINIC HYDROCARBON
 EINECS: 265-150-3
 CAS: 64742-48-9
 [F+] R12

 SODIUM SULPHONATES CAS:
 68608-26-4
 R41 CALCIUM SULPHONATES CAS: 57855-77-3 R36/38

3. HAZARDS IDENTIFICATION

Main hazards: Extremely flammable. Repeated exposure may cause skin dryness or cracking.

Other hazards: In use, may form flammable / explosive vapour-air mixture.

4. FIRST AID MEASURES (SYMPTOMS)

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness.

- **Ingestion:** Aerosol packs make the possibility of ingestion unlikely, however if this should occur, irritation of mouth/throat, nausea and stomach pain may result.
- **Inhalation:** Inhalation of high levels of vapour may cause upper respiratory tract irritation. Drowsiness or mental confusion may occur. There may be loss of consciousness.

4. FIRST AID MEASURES (ACTION)

Skin contact: Wash with soap and water. Seek medical advice if irritation develops.

Eye contact: Rinse with water for 10 minutes and seek medical advice if irritation persists.

Ingestion: If affected, seek medical advice.

ALL LUBE

Page 2

Inhalation:	Remove casualty from exposure ensuring one's own safety whilst doing so. If unconscious,				
	check for breathing and apply artificial respiration if necessary. If unconscious and breathing is				
	OK, place in the recovery position. If conscious, ensure the casualty sits or lies down. If				
	breathing becomes bubbly, have the casualty sit and provide oxygen if available. Transfer to				
	hospital as soon as possible.				
5. FIRE-FIGHTING MEASURES					
Extinguishing media:	Carbon dioxide. Alcohol or polymer foam. Dry chemical powder.				
Exposure hazards:	In combustion emits toxic fumes.				
Protection of fire-fighters:	Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin				
	and eyes.				
6. ACCIDENTAL RELEASE MEASURES					
Personal precautions:	Eliminate all sources of ignition. Mark out the contaminated area with signs and prevent access				
	to unauthorised personnel.				
Environmental precautions:	Do not discharge into drains or rivers. Contain the spillage using sufficient appropriate absorbent				
	material.				
Clean-up procedures:	If spillage is from leaking/punctured cans, ensure adequate ventilation and allow propellant to				
	evaporate. Wipe up liquid spillage with absorbent material and dispose of safely.				
7. HANDLING AND STO	RAGE				
	Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Smoking is				
Handling requirements:	Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Smoking is				
Handling requirements:	Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Smoking is forbidden.				
Storage conditions:	forbidden.				
Storage conditions: 8. EXPOSURE CONTROL	forbidden. Store in a cool, well ventilated area, below 50'C. LS / PERSONAL PROTECTION				
Storage conditions: 8. EXPOSURE CONTROL	forbidden. Store in a cool, well ventilated area, below 50°C.				
Storage conditions: 8. EXPOSURE CONTROL	forbidden. Store in a cool, well ventilated area, below 50'C. LS / PERSONAL PROTECTION NAPHTHA (PETROLEUM), HYDROTREATED HEAVY				
Storage conditions: 8. EXPOSURE CONTROL Hazardous ingredients:	forbidden. Store in a cool, well ventilated area, below 50'C. LS / PERSONAL PROTECTION NAPHTHA (PETROLEUM), HYDROTREATED HEAVY WEL (8 hr exposure limit): 1000mg/m3				
Storage conditions: 8. EXPOSURE CONTROL Hazardous ingredients:	forbidden. Store in a cool, well ventilated area, below 50'C. LS / PERSONAL PROTECTION NAPHTHA (PETROLEUM), HYDROTREATED HEAVY WEL (8 hr exposure limit): 1000mg/m3 BUTANE				
Storage conditions: 8. EXPOSURE CONTROL Hazardous ingredients:	forbidden. Store in a cool, well ventilated area, below 50'C. LS / PERSONAL PROTECTION NAPHTHA (PETROLEUM), HYDROTREATED HEAVY WEL (8 hr exposure limit): 1000mg/m3 BUTANE WEL (8 hr exposure limit): 1450 mg/m3 WEL (15 min exposure limit): 1810 mg/m3				
Storage conditions: 8. EXPOSURE CONTROL Hazardous ingredients:	forbidden. Store in a cool, well ventilated area, below 50'C. LS / PERSONAL PROTECTION NAPHTHA (PETROLEUM), HYDROTREATED HEAVY WEL (8 hr exposure limit): 1000mg/m3 BUTANE WEL (8 hr exposure limit): 1450 mg/m3 WEL (15 min exposure limit): 1810 mg/m3 PROPANE				
Storage conditions: 8. EXPOSURE CONTROL Hazardous ingredients:	forbidden. Store in a cool, well ventilated area, below 50'C. LS / PERSONAL PROTECTION NAPHTHA (PETROLEUM), HYDROTREATED HEAVY WEL (8 hr exposure limit): 1000mg/m3 BUTANE WEL (8 hr exposure limit): 1450 mg/m3 WEL (15 min exposure limit): 1810 mg/m3 PROPANE WEL (8 hr exposure limit): 1800 mg/m3 WEL (15 min exposure limit): 7200 mg/m3				
Storage conditions: 8. EXPOSURE CONTROL Hazardous ingredients: Engineering measures:	forbidden. Store in a cool, well ventilated area, below 50'C. LS / PERSONAL PROTECTION NAPHTHA (PETROLEUM), HYDROTREATED HEAVY WEL (8 hr exposure limit): 1000mg/m3 BUTANE WEL (8 hr exposure limit): 1450 mg/m3 WEL (15 min exposure limit): 1810 mg/m3 PROPANE WEL (8 hr exposure limit): 1800 mg/m3 WEL (15 min exposure limit): 7200 mg/m3 Ensure there is sufficient ventilation of the area. Do not handle in a confined space.				
Storage conditions: 8. EXPOSURE CONTROL Hazardous ingredients: Engineering measures:	forbidden. Store in a cool, well ventilated area, below 50°C. LS / PERSONAL PROTECTION NAPHTHA (PETROLEUM), HYDROTREATED HEAVY WEL (8 hr exposure limit): 1000mg/m3 BUTANE WEL (8 hr exposure limit): 1450 mg/m3 WEL (15 min exposure limit): 1810 mg/m3 PROPANE WEL (8 hr exposure limit): 1800 mg/m3 WEL (15 min exposure limit): 7200 mg/m3 Ensure there is sufficient ventilation of the area. Do not handle in a confined space. If Workplace Exposure Limit(s) listed above are exceeded, respiratory protection may be				
Storage conditions: 8. EXPOSURE CONTROL Hazardous ingredients: Engineering measures: Respiratory protection:	forbidden. Store in a cool, well ventilated area, below 50°C. ES / PERSONAL PROTECTION NAPHTHA (PETROLEUM), HYDROTREATED HEAVY WEL (8 hr exposure limit): 1000mg/m3 BUTANE WEL (8 hr exposure limit): 1450 mg/m3 WEL (15 min exposure limit): 1810 mg/m3 PROPANE WEL (8 hr exposure limit): 1800 mg/m3 WEL (15 min exposure limit): 7200 mg/m3 Ensure there is sufficient ventilation of the area. Do not handle in a confined space. If Workplace Exposure Limit(s) listed above are exceeded, respiratory protection may be required.				

ALL LUBE

9. PHYSICAL AND CHEMICAL PROPERTIES

State:	Aerosol
Colour:	Brown
Odour:	Pleasant
Oxidising:	Non-oxidising (by EC criteria)
Solubility in water:	Insoluble
Flammability limits %: lower:	0.6
upper:	9.0
Flash point°C:	-40
Autoflammability°C:	>230

10. STABILITY AND REACTIVITY

Stability:	Stable under normal conditions.		
Conditions to avoid: Heat. Sources of ignition. Flames.			
Materials to avoid:	Strong acids. Strong bases. Oxidising agents.		
Haz. decomp. products:	In combustion emits toxic fumes of carbon dioxide / carbon monoxide.		

11. TOXICOLOGICAL INFORMATION

Hazardous ingredients:	NAPHTHA (PETROLEUM), HYDROTREATED HEAVY			
	ORL RAT LD50 >5000 mg/kg			
Routes of exposure:	Exposure to high levels of vapour may cause drowsiness, dizziness, nausea, headaches,			
	vomiting. Prolonged contact with skin may cause irritation leading to dermatitis in extreme			
	cases.			

12. ECOLOGICAL INFORMATION

Mobility: Insoluble in water.

Other adverse effects: The aerosol contents are potentially harmful to aquatic organisms.

13. DISPOSAL CONSIDERATIONS

Disposal operations: Contact Uniconomy to arrange disposal. Tel 01253 854050

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

14. TRANSPORT INFORMATION

ADR / RID

UN no: 1950

Classification code: 5F

Shipping name: AEROSOLS

Labelling: 2.1



ADR Class: 2

ALL LUBE

IMDG / IMO						
UN no:	1950	Class:	2			
	F-D,S-U	Marine pollutant:				
Labelling:	2.1					
IATA / ICAO						
UN no:	1950	Class:	2			
Labelling:						
15. REGULATORY INFORMATION						
<u></u>	Extremely flammable.					
inizard symbols.						
Risk phrases:	R12: Extremely flammable.					
	R66: Repeated exposure may cause	e skin dryness or cracking.				
Safety phrases:	S2: Keep out of the reach of children	en.				
	S16: Keep away from sources of ig	nition - No smoking.				
	S23: Do not breathe vapour/spray.					
	S51: Use only in well-ventilated an					
Precautionary phrases:	Pressurized container: protect from sunlight and do not expose to temperatures exceeding					
	50°C. Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material. Keep away from sources of					
	ignition - No smoking. Keep out of	the reach of children.				
Note:	: The regulatory information given above only indicates the principal regulations specifically					
	applicable to the product described in the safety data sheet. The user's attention is drawn to					
	the possible existence of additional provisions which complete these regulations. Refer to all					
	applicable national, international a	nd local regulations or provisions.				
16. OTHER INFORMATION	DN					
Other information:	Always use in accordance with ma	nufacturer's directions.				
	This safety data sheet is prepared i	n accordance with EC Directive 2001/58	/EC.			
Risk phrases used in s.2:	R10: Flammable.					
	R65: Harmful: may cause lung dan	nage if swallowed.				
	R66: Repeated exposure may cause	e skin dryness or cracking.				
	R12: Extremely flammable.					
Legal disclaimer:	The above information is believed	to be correct but does not purport to be a	Ill inclusive and shall			
	be used only as a guide. This comp	any shall not be held liable for any dama	ge resulting from			
	handling or from contact with the a	bove product.				
				[final page]		

Page 4