

SAFETY DATA SHEET

BATTERY PROTECTOR



Page 1

Issued: 13/03/13

Revision No: 5

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

Product name: BATTERY PROTECTOR

Use / description of product: Battery terminal protector/indicator.

Company name: Uniconomy Ltd
Unit 4 Chester Court
Red Marsh Drive
Thornton Cleveleys
Lancashire
FY5 4HP
Tel: 01253 854050
Fax: 01253 854049

2. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous ingredients: ODOURLESS KEROSENE 30-50%
EINECS: 265-149-8 CAS: 064742-47-8
[Xn] R65; [N] R51/53

- BUTANE 10-30%
EINECS: 203-448-7 CAS: 106-97-8
[F+] R12
- PROPANE 10-30%
EINECS: 200-827-9 CAS: 74-98-6
[F+] R12

3. HAZARDS IDENTIFICATION

Main hazards: Extremely flammable. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Other hazards: In use, may form flammable / explosive vapour-air mixture.

4. FIRST AID MEASURES (SYMPTOMS)

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: Aerosol packs make the possibility of ingestion unlikely, however if this should occur, irritation of mouth/throat, nausea and stomach pain may result.

Inhalation: Inhalation of high levels of vapour may cause upper respiratory tract irritation. Prolonged inhalation of vapour may cause drowsiness, dizziness, or headache.

4. FIRST AID MEASURES (ACTION)

Skin contact: Wash with soap and water. Seek medical advice if irritation develops.

Eye contact: Rinse with water for 10 minutes and seek medical advice if irritation persists.

[cont...]

SAFETY DATA SHEET
BATTERY PROTECTOR

Ingestion: If affected, seek medical advice.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. If unconscious, check for breathing and apply artificial respiration if necessary. If unconscious and breathing is OK, place in the recovery position. If conscious, ensure the casualty sits or lies down. If breathing becomes bubbly, have the casualty sit and provide oxygen if available. Transfer to hospital as soon as possible.

5. FIRE-FIGHTING MEASURES

Extinguishing media: Carbon dioxide. Alcohol or polymer foam. Dry chemical powder.

Exposure hazards: Extremely flammable. Vapour may travel considerable distance to source of ignition and flash back. Forms explosive air-vapour mixture.

Protection of fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions: Eliminate all sources of ignition. Mark out the contaminated area with signs and prevent access to unauthorised personnel.

Environmental precautions: Contain the spillage using sufficient appropriate absorbent material.

Clean-up procedures: If spillage is from leaking/punctured cans, ensure adequate ventilation and allow propellant to evaporate. Wipe up liquid spillage with absorbent material and dispose of safely.

7. HANDLING AND STORAGE

Handling requirements: Ensure there is sufficient ventilation of the area. Avoid direct contact with the substance. Smoking is forbidden.

Storage conditions: Store in a cool, well ventilated area, below 50°C. Keep away from sources of ignition.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Hazardous ingredients: ODOURLESS KEROSENE

WEL (8 hr exposure limit): 1000mg/m³

- BUTANE

WEL (8 hr exposure limit): 1450 mg/m³ WEL (15 min exposure limit): 1810 mg/m³

- PROPANE

WEL (8 hr exposure limit): 1800 mg/m³ WEL (15 min exposure limit): 7200 mg/m³

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: If Workplace Exposure Limit(s) listed above are exceeded, respiratory protection may be required.

Hand protection: Protective gloves.

Eye protection: Safety goggles.

Skin protection: Protective overalls.

SAFETY DATA SHEET
BATTERY PROTECTOR**9. PHYSICAL AND CHEMICAL PROPERTIES****State:** Aerosol**Colour:** Orange-red**Odour:** Paraffinic**Oxidising:** Non-oxidising (by EC criteria)**Solubility in water:** Insoluble**Flammability limits %: lower:** 0.8**upper:** 9.0**Flash point°C:** -40**10. STABILITY AND REACTIVITY****Stability:** Stable under normal conditions.**Conditions to avoid:** Hot surfaces. Sources of ignition. Flames.**Materials to avoid:** Oxidising agents.**11. TOXICOLOGICAL INFORMATION****Routes of exposure:** Exposure to high levels of vapour may cause drowsiness, dizziness, nausea, headaches, vomiting. Prolonged contact with skin may cause irritation leading to dermatitis in extreme cases.**12. ECOLOGICAL INFORMATION****Hazardous ingredients:** ODOURLESS KEROSENE
ALGAE 72H IC50 20 ppm
DAPHNIA 24H EC50 >250 ppm
FISH 96H LC50 >1000 ppm**Mobility:** Insoluble in water.**Other adverse effects:** The aerosol contents are potentially harmful to aquatic organisms.**13. DISPOSAL CONSIDERATIONS****Disposal operations:** Contact Uniconomy Ltd to arrange disposal.**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.**14. TRANSPORT INFORMATION****ADR / RID****UN no:** 1950**ADR Class:** 2**Classification code:** 5F**Shipping name:** AEROSOLS**Labelling:** 2.1

SAFETY DATA SHEET
BATTERY PROTECTOR

IMDG / IMO

UN no: 1950 **Class:** 2
EmS: F-D,S-U **Marine pollutant:** .
Labelling: 2.1

IATA / ICAO

UN no: 1950 **Class:** 2
Labelling: 2.1

15. REGULATORY INFORMATION

Hazard symbols: Extremely flammable.
 Dangerous for the environment.



Risk phrases: R12: Extremely flammable.
 R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Safety phrases: S2: Keep out of the reach of children.
 S23: Do not breathe vapour/spray.
 S51: Use only in well-ventilated areas.
 S61: Avoid release to the environment. Refer to special instructions / safety data sheets.

Precautionary phrases: Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.
 Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking. Keep out of the reach of children.

Note: The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions.

16. OTHER INFORMATION

Other information: Always use in accordance with manufacturer's directions.
 This safety data sheet is prepared in accordance with EC Directive 2001/58/EC.

Risk phrases used in s.2: R65: Harmful: may cause lung damage if swallowed.
 R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
 R12: Extremely flammable.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall

SAFETY DATA SHEET

BATTERY PROTECTOR

be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.